

I250-IT4501 Cisliano LubProd
Via per Abbiategrasso
Cisliano
20080
Italy



Certificate of Analysis

Material

Material Description

Batch Number

550043647

Shell Omala S4 WE 150 1*20L

12520830

Date Manufactured

Date Tested

11 Jul 2025

15 Jul 2025

Test Description	Result	Unit	Method
Viscosity Kinematic 40°C	153,30	mm2/s	ASTM D445
Appearance	Normal	-	VISUAL
Density 15°C (by Densitymeter)	1070,0	kg/m3	ASTM D1298
Pour Point	-42	CEL	ASTM D97
Foam Chara.(Seq.I),Tendency	0	ml	ASTM D892
Foam Chara.(Seq.I),Stablity	0	ml	ASTM D892
Foam.Chara.(Seq.II),Tendency	10	ml	ASTM D892
Foam. Chara.(Seq.II),Stablity	0	ml	ASTM D892
Foam.Chara.(Seq.III),Tendency	0	ml	ASTM D892
Foam.Chara.(Seq.III),Stablity	0	ml	ASTM D892

Date

Certified by

Preferred contact

17 Jul 2025

Giulio Bellini

+ 390290399437

Cisliano LOBP maintains a Quality Control System to ensure product supplied meets required specifications.
Certified to EN ISO 9001 and ISO 14001