

I250-IT4501 Cisliano LubProd
Via per Abbiategrasso
Cisliano
20080
Italy



Certificate of Analysis

Material

Material Description

Batch Number

550043652

Shell Omala S4 WE 320 1*20L

12494442

Date Manufactured

Date Tested

16 May 2025

23 May 2025

Test Description	Result	Unit	Method
Viscosity Kinematic 40°C	310,10	mm2/s	ASTM D445
Appearance	Normal	-	VISUAL
Density 15°C (by Densitymeter)	1066,7	kg/m3	ASTM D1298
Pour Point	-42	CEL	ASTM D97
Foam Chara.(Seq.I),Tendency	20	ml	ASTM D892
Foam Chara.(Seq.I),Stablity	0	ml	ASTM D892
Foam.Chara.(Seq.II),Tendency	50	ml	ASTM D892
Foam. Chara.(Seq.II),Stablity	0	ml	ASTM D892
Foam.Chara.(Seq.III),Tendency	30	ml	ASTM D892
Foam.Chara.(Seq.III),Stablity	0	ml	ASTM D892

Date

Certified by

Preferred contact

29 May 2025

Giulio Bellini

+ 390290399437

Cisliano LOBP maintains a Quality Control System to ensure product supplied
meets required specifications.
Certified to EN ISO 9001 and ISO 14001