

T124-TR4500 Derince LubProd
Petrol Ofisi Caddesi
Kocaeli
41900
Turkey



Certificate of Analysis

Material

Material Description

Batch Number

550026236

Shell Tellus S2 V 32 1*209L

12447143

Date Manufactured

Date Tested

17 March 2025

18 March 2025

Test Description	Result	Unit	Method
Viscosity Kinematic 40°C	32,78	mm2/s	ASTM D445
Viscosity Index	140	*****	ASTM D2270
Appearance	Clear and Bright	-	VISUAL
Density 15°C (by Densitymeter)	869,0	kg/m3	ASTM D4052
Pour Point	-39	CEL	ASTM D97
Demulsibility 54°C	20	min	ASTM D1401
Foam Chara.(Seq.I),Tendency	100	ml	ASTM D892
Foam Chara.(Seq.I),Stablity	0	ml	ASTM D892
Filterability Factor	104,0	*****	TMS 371
Particle Count 1	20	*****	ISO 4406
Particle Count 2	19	*****	ISO 4406
Particle Count 3	13	*****	ISO 4406

Date

Certified by

Preferred contact

20 March 2025

+902623171826

We hereby confirm that the products supplied have been tested and conform to the quality requirements laid down by Shell International Petroleum Company Limited, London. This Quality System is certified against ISO 9001 and IATF 16949 standards.