

D133-DE4500 Grasbrook LubProd
Woerthdamm 32
Hamburg
20457
Germany



Certificate of Analysis

Material

Material Description

Batch Number

550045738

Tellus S2 VX 32 1*20L

12423050

Date Manufactured

Date Tested

08 Jan 2025

08 Jan 2025

Test Description	Result	Unit	Method
Viscosity Kinematic 40°C	31,35	mm2/s	ISO 3104
Viscosity Index	145	*****	ISO 2909
Appearance	Clear and Bright	-	VISUAL
Density 15°C (by Densitymeter)	850,1	kg/m3	ISO 12185
Pour Point	-45	CEL	ASTM D5950
Demulsibility 54°C	10	min	ISO 6614
Foam Chara.(Seq.I),Tendency	10	ml	ASTM D892
Foam Chara.(Seq.I),Stablity	0	ml	ASTM D892
Filterability Factor	104,0	*****	TMS 371
Viscosity Kinematic 100°C	6,084	mm2/s	ISO 3104

Date

Certified by

Preferred contact

10 Jan 2025

Eric Froboese

+ 49(0)40809080504

Grasbrook Lubricants Centre maintains a Quality Control System to ensure product supplied meets required specifications.Certified to DIN EN ISO 9001:2015
This CoA conforms with DIN EN 10204 acc. 3.1

This document has been produced electronically and is valid without signature#